

**SAFETY DATA SHEET**

**SECTION 1 : IDENTIFICATION**

Product identifier used on the label:

Product Name: **BeakGuard**

Other means of identification:

Recommended use of the chemical and restrictions on use:

Chemical manufacturer address and telephone number:

Manufacturer Name: Stuc-O-flex International, Inc  
Address: 17635 NE 67th Court  
Redmond, WA 98052  
USA  
Website: www.stucoflex.com  
General Phone Number: 800-305-1045  
General Fax Number: 425-869-0107  
Customer Service Phone Number: 425-885-5085  
Technical Product Information: 425-885-5085

Emergency phone number:

Emergency Phone Number: CHEMTREC 1-800-424-9300

**SECTION 2 : HAZARD(S) IDENTIFICATION**

Classification of the chemical in accordance with CFR 1910.1200(d)(f):

Signal Word: Not applicable.  
GHS Class: Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200..  
Hazard Statements: Not applicable.  
Precautionary Statements: Not applicable.

Hazards not otherwise classified that have been identified during the classification process:

Potential Health Effects:

Eye: Causes eye irritation.  
Skin: Causes skin irritation.  
Inhalation: Prolonged or excessive inhalation may cause respiratory tract irritation.  
Ingestion: May be harmful if swallowed. May cause vomiting.  
Chronic Health Effects: Prolonged or repeated contact may cause skin irritation.  
Signs/Symptoms: Overexposure may cause headaches and dizziness.  
Target Organs: Eyes. Skin. Respiratory system. Digestive system.  
Aggravation of Pre-Existing Conditions: None generally recognized.

**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**

Mixtures:

Chemical Name	CAS#	Ingredient Percent	EC Num.
Acrylic polymer(s)	No Data	20 - 30 by weight	
Water	7732-18-5	40 - 45 by weight	

Potassium Tripolyphos	13845-36-8	0.1 - 0.2 by weight	237-574-9
Diuron	330-54-1	0.1 - 0.5 by weight	
Diphenyl Ketone	119-61-9	0.1 - 0.5 by weight	204-337-6
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	0.1 - 1.0 by weight	265-169-7
Propylene glycol	57-55-6	1 - 5 by weight	200-338-0
Limestone	1317-65-3	1 - 5 by weight	215-279-6
MICA	12001-26-2	5 - 10 by weight	
Titanium dioxide	13463-67-7	10 - 15 by weight	236-675-5

## SECTION 4 : FIRST AID MEASURES

### Description of necessary measures:

<b>Eye Contact:</b>	Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Remove contacts if present and easy to do. Continue rinsing. Get medical attention, if irritation or symptoms of overexposure persists.
<b>Skin Contact:</b>	Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
<b>Inhalation:</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
<b>Ingestion:</b>	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

## SECTION 5 : FIRE FIGHTING MEASURES

### Suitable and unsuitable extinguishing media:


<b>Suitable Extinguishing Media:</b>	Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving this material.
--------------------------------------	--

### Special protective equipment and precautions for fire-fighters:

<b>Protective Equipment:</b>	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.
------------------------------	---

### **NFPA Ratings:**

NFPA Health:	1
NFPA Flammability:	1
NFPA Reactivity:	0



## SECTION 6 : ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures:

<b>Personal Precautions:</b>	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use proper personal protective equipment as listed in Section 8.
------------------------------	---

### Environmental precautions:

<b>Environmental Precautions:</b>	Avoid runoff into storm sewers, ditches, and waterways.
-----------------------------------	---

### Methods and materials for containment and cleaning up:

<b>Methods for containment:</b>	Contain spills with an inert absorbent material such as soil or sand. Prevent from spreading by covering, diking or other means. Provide ventilation.
<b>Methods for cleanup:</b>	Clean up spills immediately observing precautions in the protective equipment section. Place into a suitable container for disposal. Provide ventilation. After removal, flush spill area with soap and water to remove trace residue.

## SECTION 7 : HANDLING and STORAGE

### Precautions for safe handling:

<b>Handling:</b>	Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing.
<b>Hygiene Practices:</b>	Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

Conditions for safe storage, including any incompatibilities:

**Storage:** Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and incompatible substances. Keep container tightly closed when not in use.

## SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE GUIDELINES:

MICA :

Guideline ACGIH: TLV-TWA: 3 mg/m<sup>3</sup> (R)

Guideline OSHA: PEL-TWA: 20 mppcf

Titanium dioxide :

Guideline ACGIH: TLV-TWA: 10 mg/m<sup>3</sup>

Appropriate engineering controls:

**Engineering Controls:** Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

Individual protection measures:

**Eye/Face Protection:** Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.

**Skin Protection Description:** Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.

**Respiratory Protection:** A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

**Other Protective:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

**PPE Pictograms:**



## SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL AND CHEMICAL PROPERTIES:

<b>Physical State:</b>	Viscous liquid
<b>Physical State Appearance:</b>	Thick Liquid.
<b>Color:</b>	Various Colors.
<b>Odor:</b>	Slight latex odor
<b>Odor Threshold:</b>	No Data
<b>Boiling Point:</b>	212°F
<b>Melting Point:</b>	No Data
<b>Density:</b>	10.0 - 10.8
<b>Specific Gravity:</b>	1.20 - 1.30
<b>Specific Volume:</b>	No Data
<b>Solubility:</b>	Water thinnable
<b>Vapor Density:</b>	No Data
<b>Vapor Pressure:</b>	No Data
<b>Percent Volatile:</b>	46.0 - 50.0
<b>Evaporation Rate:</b>	No Data
<b>Evaporation Point:</b>	No Data
<b>pH:</b>	8.0 - 9.0
<b>Molecular Formula:</b>	Mixture
<b>Molecular Weight:</b>	Not applicable.
<b>Viscosity:</b>	5000 - 5300 cP
<b>Coefficient of Water/Oil Distribution:</b>	No Data
<b>Flammability:</b>	No Data
<b>Flash Point:</b>	No Data
<b>Lower Flammable/Explosive Limit:</b>	Not applicable.

Upper Flammable/Explosive Limit:	Not applicable.
Explosive Properties:	Not explosive.
Oxidizing Properties:	No Data
Refractive Index:	Not applicable.
Optical Rotation:	Not applicable.
VOC Content:	< 100 g/L (less water)

## SECTION 10 : STABILITY and REACTIVITY

### Chemical Stability:

**Chemical Stability:** Stable under normal temperatures and pressures.

### Possibility of hazardous reactions:

**Hazardous Polymerization:** Not reported.

### Conditions To Avoid:

**Conditions to Avoid:** Heat, flames, incompatible materials, and freezing or temperatures below 32 deg. F.

### Incompatible Materials:

**Incompatible Materials:** Oxidizing agents. Strong acids and alkalis.

## SECTION 11 : TOXICOLOGICAL INFORMATION

### TOXICOLOGICAL INFORMATION:

#### Water :

**Ingestion:** Oral - Rat LD50 - Lethal dose, 50 percent kill: >90 mL/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

#### Diuron :

**Eye:** corrosive

**Skin:** Administration onto the skin - Rat LD50 - Lethal dose, 50 percent kill: >5 gm/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

**Ingestion:** Oral - Rat LD50 - Lethal dose, 50 percent kill: 1017 mg/kg [Behavioral - General anesthetic Behavioral - Ataxia]  
Oral - Rat LD50 - Lethal dose, 50 percent kill: 1 gm/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

#### Diphenyl Ketone :

**Skin:** Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: 3535 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

**Ingestion:** Oral - Rat LD50 - Lethal dose, 50 percent kill: >10 gm/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

**Chronic Effects:** Normal application procedures for this product pose minimal hazard as to the release of diphenyl ketone dust, but grinding or sanding dried films of this product may yield some respirable particulates.

**Carcinogenicity:** IARC: Group 2B: Possibly carcinogenic to humans.

#### Petroleum distillates, solvent dewaxed heavy paraffinic :

**Skin:** Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: >5000 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

**Ingestion:** Oral - Rat LD50 - Lethal dose, 50 percent kill: >5000 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

#### Propylene glycol :

**Eye:** Administration into the eye - Rabbit Standard Draize test: 100 mg [Mild]  
Administration into the eye - Rabbit Standard Draize test: 500 mg/24H [Mild] (RTECS)

**Skin:** Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: 20800 mg/kg [Details of toxic effects not reported other than lethal dose value]  
Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: 20800 mg/kg [Behavioral - Ataxia Behavioral - Tetany Lungs, Thorax, or Respiration - Respiratory depression] (RTECS)

**Ingestion:** Oral - Rat LD50 - Lethal dose, 50 percent kill: 20 gm/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

#### Titanium dioxide :

**Chronic Effects:** Normal application procedures for this product pose no hazard as to the release of respirable titanium dioxide dust, but grinding or sanding dried films of this product may yield some respirable titanium dioxide. Although IARC has classified titanium dioxide as possible carcinogenic to human (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products which titanium dioxide is bound to other materials". OSHA does not regulate titanium dioxide as a carcinogen. However, under 29CFR 1910.1200 the SDS must convey the fact that titanium dioxide is a potential carcinogen to rats.

**Carcinogenicity:** Animal evidence shows that high concentrations of pigment-grade (powdered) and ultrafine titanium dioxide dust caused respiratory tract cancer in rats exposed by inhalation.

## SECTION 12 : ECOLOGICAL INFORMATION

### Ecotoxicity:

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

### Diuron :

#### Ecotoxicity:

Ecotoxicity: acute toxicity to fish, aquatic invertebrates, algae and aquatic plants.

## SECTION 13 : DISPOSAL CONSIDERATIONS

### Description of waste:

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

## SECTION 14 : TRANSPORT INFORMATION

DOT Shipping Name: Not restricted as a dangerous good.

DOT UN Number: Not restricted as a dangerous good.

IATA Shipping Name: Not restricted as a dangerous good.

IATA UN Number: Not restricted as a dangerous good.

Canadian Shipping Name: Not restricted as a dangerous good.

Canadian UN Number: Not restricted as a dangerous good.

IMDG UN Number : Not restricted as a dangerous good.

IMDG Shipping Name : Not restricted as a dangerous good.

ADR UN Number: Not restricted as a dangerous good.

ADR Shipping Name : Not restricted as a dangerous good.

## SECTION 15 : REGULATORY INFORMATION

### Safety, health and environmental regulations specific for the product:

#### Potassium Tripolyphos :

TSCA Inventory Status: Listed

Canada DSL: Listed

EC Number: 237-574-9

#### Diuron :

California PROP 65: Listed

#### Diphenyl Ketone :

TSCA Inventory Status: Listed

California PROP 65: Listed: cancer.

Canada DSL: Listed

EC Number: 204-337-6

#### Petroleum distillates, solvent dewaxed heavy paraffinic :

TSCA Inventory Status: Listed

Canada DSL: Listed

EC Number: 265-169-7

#### Propylene glycol :

TSCA Inventory Status: Listed

Canada DSL: Listed

EC Number: 200-338-0

**Limestone :**

TSCA Inventory Status: Listed

EC Number: 215-279-6

**MICA :**

Canada DSL: Listed

**Titanium dioxide :**

TSCA Inventory Status: Listed

Canada DSL: Listed

EC Number: 236-675-5

**SECTION 16 : ADDITIONAL INFORMATION**

**HMIS Ratings:**

HMIS Health Hazard: 1  
HMIS Fire Hazard: 1  
HMIS Reactivity: 0  
HMIS Personal Protection: X

<b>Health Hazard</b>	<b>1</b>
<b>Fire Hazard</b>	<b>1</b>
<b>Reactivity</b>	<b>0</b>
<b>Personal Protection</b>	<b>X</b>

SDS Creation Date: July 30, 2015

SDS Revision Date: May 22, 2019

SDS Format:

SDS Author: Actio Corporation

**Disclaimer:** The information contained herein is, to the best of Stuc-o-flex International, Inc. knowledge, accurate as of the data indicated. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume responsibility for the results of its use. This information is furnished on the condition that the person receiving it shall make his own determination as to the suitability of the material for his particular purpose and on the condition that he assumes the risk of his use thereof.

Copyright© 1996-2018 Enviance. All Rights Reserved.