

SPECIFICATIONS – BIRD SLOPE™

PART 1 – GENERAL

1.1 SUMMARY

- A. Design Requirements: Select appropriate size and system as determined by site conditions to prevent birds from landing and roosting on specified surfaces.

1.2 QUALITY ASSURANCE

- A. Single Source Responsibility: Furnish products from one manufacturer for entire project.
- B. Country of Origin: Country of Origin shall be designated at U.S.A.
- C. Obtain all technical information from the manufacturer.
- D. Utilize labor or Bird-B-Gone Authorized Installers who are knowledgeable in Bird-B-Gone, Inc. product installations.
- E. Installer shall visit the site to gather all information of existing site conditions.

1.3 SUBMITTALS

- A. Product Data: Submit manufacturer's descriptive literature and product specifications for each product including catalogs, installation instructions other descriptive material.
- B. Provide Warranty on Material and Installation.
- C. Provide Samples of Bird Slope excluding proposed fastening methods.
- D. Provide statement by official indicating that they are a certified installation company.

1.4 PRODUCT HANDLING

- A. Protect Bird-B-Gone, Inc. products from damage before, during and after the installation.

1.5 PROJECT CONDITIONS

- A. Coordination: Furnish samples of system(s) so installation can be coordinated with existing conditions and within on-site conditions.
- B. Visit site and field measure prior to fabrication and delivery of materials.

1.6 WARRANTY

- A. Product shall carry a minimum 2-year guarantee against U.V. breakdown.

PART 2 – PRODUCTS

2.1 ACCEPTABLE MANUFACTURER

Manufacturer:

Bird-B-Gone, Inc.

Bird Slope™

15375 Barranca Pkwy #D

Irvine, CA 92618

Tel: 800-392-6915 or 949-472-3122

Fax: 949-472-3116

P.O.C.: Chris Fields

2.2 PRODUCT DESCRIPTION

- A. Model Designation:
 - 1. BIRD SLOPE™
 - a. Width of Coverage: 5.5 inches
 - b. Length: 4 ft. sections
 - c. Packaging: 48ft. per box. (12) 4ft. sections per box.
 - d. Colors: Grey or Stone. Can be painted to match desired color.
 - e. Width of Coverage with Extender: 10 inches
 - f. Length of Extender: 4 ft. sections
 - g. End Caps: Use to close off ends of installations as necessary.
 - h. Mounting System: As determined by the manufacturer and based on project conditions.
- B. Product made in the U.S.A.

2.3 MATERIALS

- A. Material: U.V. protected outdoor grade PVC plastic (sun & weather resistant).
- B. Construction: Rigid one-piece construction.
- C. Adaptation: Cut to desired width / length using tablesaw, hacksaw or tin snips.

2.4 MOUNTING SYSTEMS

- A. Use an outdoor construction adhesive that is not silicone based. Purchase from the manufacturer or call for recommended adhesives.
- B. For under eave installations use Bird Slope Mounting Clips.

PART 3 – EXECUTION

3.1 EXAMINATION

- A. Examine the installation area and note any detrimental or hazardous work conditions. Notify contracting officer or inspector of the detrimental work conditions.
- B. Do not proceed with installation until conditions are corrected.

3.2 SURFACE PREPARATION

- A. Surface should be thoroughly cleaned and free of bird droppings, nesting materials, rust, peeling paint or other debris.
- B. Remove or repair articles that may damage Bird Slope™ after installation, including overhanging foliage, brush and loose parts on the structure.

3.3 INSTALLATION

- A. Install Bird Slope™ as recommended by the manufacturer.
- B. Bird Slope™ should be installed correctly, covering the entire depth of the surface.
 - 1. Follow the contours and angles closely.
 - 2. Space materials in accordance with manufacturer's recommendations.
 - 3. Use End Caps to close off where necessary.

3.4 INSPECTION

- A. Visually inspect Bird Slope™ for any signs of poor installation, including loose fasteners and un-removed debris.
- B. Immediately correct and repair as necessary.

END OF SPECIFICATONS